

DATA SHEET

VOCIA® VO-4

OUTPUT DEVICE



The VO-4 is a networked audio output expansion device allowing the user to add four line-level CobraNet® output channels to a Vicia® system. The VO-4 features embedded DSP and on-board memory to process and store all device-specific configuration information locally and includes comprehensive fixed-chain digital-signal processing. As part of the Vicia system, the VO-4 meets paging requirements for facilities of all sizes.

FEATURES

- Converts Vicia digital audio to industry standard CobraNet outputs
- Four removable terminal block connectors for line-level outputs
- Four control inputs and four control outputs
- Software-configurable local audio signal processing, including gain, filters, and compressor/limiter
- Rotary switches for unit identification
- Power Over Ethernet (PoE)
- CobraNet audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Status LEDs to indicate signal and clip
- CE marked, UL listed and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The audio output device shall be designed exclusively for use with Biamp® Vicia systems. It shall be rack mountable (1RU) and provide audio and control via CobraNet.® It shall receive Power over Ethernet (PoE) utilizing a single (CAT5) network cable to a rear panel RJ45 connector. The output device shall provide four removable terminal block connectors for line-level audio outputs, four control inputs, and four control outputs. The audio output device shall provide local digital audio signal processing and local storage of configuration data. The audio output device shall indicate signal and clip with LEDs on the front panel. The audio output device shall be CE marked, UL listed and shall be compliant with the RoHS directive. Warranty shall be five years. The output device shall be a Vicia VO-4.

VOCIA VO-4 SPECIFICATIONS

Network Connection:	RJ45 with shielded Ethernet (CAT5, CAT5e, CAT6, or CAT 7)	Control Outputs:	Single Form C voltage free change over contact
Frequency Response (20Hz-20kHz):	± 1dB	Type:	125V AC, 60V DC
THD+N (20Hz-8kHz):	<0.02%	Max Operating Voltage:	37 VA
Dynamic Range:	> 100dB	Max Switching Capacity:	10µA 10mV DC
Crosstalk (10kHz):	> 80dB	Min Operating Load:	
Maximum Load Impedance:	600kΩ	Dimensions:	
Nominal Output Level:	-10dBu, 0dBu, +4dBu (selectable)	Height:	1.75 inches (44.5 mm)
Maximum Output Level:	+22dBu	Width:	19 inches (483 mm)
Maximum Output Load:	2kΩ	Depth:	10 inches (254 mm)
Power:	802.3af (PoE) Class 3	Weight:	6.4 lbs. (2.9 kg)
Control Inputs:		Environment:	
Type:	Digital, variable threshold	Ambient Operating Temperature Range:	23-104° F (-8 - 42° C)
Max Input Threshold:	10V	Humidity:	0 - 95% non-condensing
Max Input Voltage:	12V	Altitude:	0 - 10,000 Feet (0 - 3000 Meters) MSL
Min Input Threshold:	150mV	Sample Rate:	48kHz
Input Impedance:	100kΩ	A/D Converters:	24-bit
		Compliance:	FCC Part 15B (USA) CE marked (Europe) UL and C-UL Listed (USA and Canada) RoHS Directive (Europe)

VOCIA VO-4 BACK PANEL

