PXL118

Hybrid-Horn Subwoofer





- High SPL with good Low End
- Stunning impulse response accuracy
- Dynamic bass even under high SPL loads
- Long excursion 18"/100mm VC speaker
- 2 cabinets configurations for optimal coupling

OVERVIEW

The PXL118 makes use of a Hybrid design to achieve high maximum sound pressure while producing deep low bass well below 50 Hz. Even under maximum load the impulse response accuracy is striking.

The PXL118 is a subwoofer with a rich, punchy sound, specifically designed to match the PXH64 mid/high speaker extending its frequency response down to 50 Hz. Its cabinet shape, size and flying arrangements are totally compatible with the PXH64.

To achieve the highest possible sound pressure levels, the PXL118 is conceived an hibrid bass horn and armed with a very powerfull, long excursion, 100mm voice-coil, 18" woofer for precisely and powerfull bass without any dynamic loss even under high SPL loads.

TECHNICAL SPECIFICATIONS

Technical Data	
Speaker Type:	Hybrid Horn-Loaded Bass Speaker
Acoustical Data	
Frequency Response (-6dB):	42Hz - 180Hz
Low Frequency Extension (-10dB):	34Hz
Sensitivity (1W@1m):	104dB (Half-space)
Calculated Max. SPL (Cont/Peak):	137.8dB/143.8dB (Half-Space)
Drivers	
Loudspeakers:	1 x 18" (460mm)/4" (100mm) VC, high excursion, B&C custom speaker
Electrical Data	
Program/Peak Power:	2400W/4800W (10ms)
Nominal Impedance:	8
Nominal Impedance: Recommended Amplifier:	8 PXA8001 (Dedicated power rack)
Recommended Amplifier:	PXA8001 (Dedicated power rack)
Recommended Amplifier: Connectors:	PXA8001 (Dedicated power rack)
Recommended Amplifier: Connectors: Enclosure	PXA8001 (Dedicated power rack) 2 x Neutrik NL8 parallel wired
Recommended Amplifier: Connectors: Enclosure Construction:	PXA8001 (Dedicated power rack) 2 x Neutrik NL8 parallel wired Braced 15mm multi-laminate birch ply
Recommended Amplifier: Connectors: Enclosure Construction: Finish:	PXA8001 (Dedicated power rack) 2 x Neutrik NL8 parallel wired Braced 15mm multi-laminate birch ply Textured black semi-matte coating
Recommended Amplifier: Connectors: Enclosure Construction: Finish: Protective grill:	PXA8001 (Dedicated power rack) 2 x Neutrik NL8 parallel wired Braced 15mm multi-laminate birch ply Textured black semi-matte coating Black perforated steel 16 x M8 threaded inserts for optional wheel kit, 12 x M8 threaded inserts for optional
Recommended Amplifier: Connectors: Enclosure Construction: Finish: Protective grill: Fittings:	PXA8001 (Dedicated power rack) 2 x Neutrik NL8 parallel wired Braced 15mm multi-laminate birch ply Textured black semi-matte coating Black perforated steel 16 x M8 threaded inserts for optional wheel kit, 12 x M8 threaded inserts for optional rigging system